

OPEN
IN

uni_one STANDARD

DOUBLE GLAZING **U_w=1,2 W/m²K**



Material		Wood-Aluminium
Thermal insulation		U _w = 1,2 W/m ² K
Insulating glass		Double glazing thickness 28-32mm
Acoustic insulation		R _w up to 40 dB
Security hardware		Up to RC2
Dimensions in mm.		
Thickness of sash		83,5 x 70mm
Thickness of frame		77,5 x 70mm
Visible section sash + frame		106mm
Visible section middle clamp		116mm
Air permeability		CLASS 4
Water tightness		CLASS E1050
Wind load resistance		CLASS C5

The thermal transmittance values are calculated according to UNI EN 10077/1-2018, UNI EN 10077/2-2018, UNI EN 10456-2008, UNI EN 673-2011 standards, in reference to a window with 1 sash WxH (1230x1480mm, $\psi_g = 0,04$ W/mK)

The air-water-wind tightness performances are certified in reference to a window with 2 sashes WxH (1500x1500mm)

The acoustic insulation values are certified in reference to a window with 2 sashes WxH (1500x1500mm)



**STANDARD - 28mm glass
SOFT WOOD
U_f = 1,2 W/m²K**

U _g W/m ² K		U _w W/m ² K
1,0	->	1,2
1,1	->	1,2
1,2	->	1,3
1,3	->	1,4
1,4	->	1,4
1,5	->	1,5
1,6	->	1,6